



# International Journal of Engineering Research and Science & Technology

ISSN : 2319-5991  
Vol. 4, No. 2  
May 2015



[www.ijerst.com](http://www.ijerst.com)

Email: [editorijerst@gmail.com](mailto:editorijerst@gmail.com) or [editor@ijerst.com](mailto:editor@ijerst.com)

Research Paper

# IMPROVEMENT AND VALIDATION OF VISION BASED AUTONOMOUS ROBOT

R Mahalakshmi<sup>1\*</sup>, R Pavithra<sup>1</sup>, Poorvaja Shankar<sup>1</sup>, G Kannan<sup>1</sup> and P Thamarai<sup>1</sup>

\*Corresponding Author: **R Mahalakshmi** ✉ mahalakshmi2228@gmail.com

As we are all mindful, significant undertakings in Military are similarly more unsafe than different applications. For instance: While strolling through minefields, the troopers on obligation need to deactivate unexploded bombs or most extreme consideration to be taken while clearing structures and so on. In such a circumstance, self-ruling robots help to complete the above operations all the more proficiently. Nonetheless, finish self-sufficient robots that can perform mixed bag of such assignments are still a work in progress. Specialist's world over work energetically to outline and grow such robots with a specific end goal to rearrange our work in different fields. The initial move towards attaining to self-governance of a robot is configuration and improvement of impediment evasion and way arranging. For this, observation cams can be utilized in the arrangement locale for vision based target identification.

**Keywords:** Reconnaissance, Vision, Target discovery, AVI, Remote cam

## INTRODUCTION

In existing framework the conventional tanker is restricted insight and primarily worked by human administrator. Likewise the system configuration is displaying as a 2 (level of opportunity) robot arm, which is fairly limited in working introduction edges. The downsides of the current framework are moderate reaction, additional time expended and human misfortune. In proposed framework this paper displays the outline, advancement and acceptance of vision based self-ruling automated framework for military applications. The preferences of proposed framework are remote control and observing, sparing the officers life and

more effective reconnaissance. This robot can be utilized as a part of military tanks and utilized for mine discovery.

## BLOCK EXPLANATION

### Robot Section

Robot segment comprises of ARM micro-controller, CCTV cam, LCD, RFID peruser, ULN 2003A, area mine recognition, zigbee.


CCTV remains for Closed Circuit TV. CCTV utilizes one or more camcorders to transmit feature pictures and here and there sound pictures to a screen, set of screens or feature recorder. Most remote CCTV cams utilize the 2.4

<sup>1</sup> Bharath University, 173, Agharam Road, Selaiyur, Chennai, Tamil Nadu 600073, India.

Gigahertz frequencies to transmit their feature pictures to a screen or DVR (computerized feature recorder). As a rule, frequencies can be marginally changed to have more than one gathering of cams in a particular space. Remote CCTV cams utilized at this recurrence can without much of a stretch transmit through most dividers and snags; however every individual area will have its own working points of confinement. Expect most remote CCTV cams to send information to a scope of around 200 feet, however numerous will more probable function admirably when transmitting under 150 feet. An unmistakable viewable pathway transmission will dependably work the best. Clearly a remote association permits you more prominent opportunity to place your CCTV cam anyplace. While remote CCTV cams transmit their feature pictures to an advanced feature recorder or screen, large portions of these sorts of cams must be connected to an electrical outlet. There is however some CCTV cams that are battery worked.

A RFID peruser is a gadget that is utilized to question a RFID tag. The peruser has a reception apparatus that discharges radio waves; the tag reacts by sending back its information. A RFID tag is a microchip consolidated with a receiving wire in a conservative bundle; the bundling is organized to permit the RFID tag to be appended to an item to be followed. "RFID" remains for Radio Frequency Identification. The label's receiving wire grabs signals from a RFID peruser or scanner and afterward gives back the sign, as a rule with some extra information (like an interesting serial number or other modified data). An aloof tag is a RFID label that does not contain a battery; the force is supplied by the peruser. At the point when radio waves from the peruser are

experienced by a latent RFID label, the wound receiving wire inside the label structures an attractive field. The label draws power from it, invigorating the circuits in the tag. The label then sends the data encoded in the label's memory. The  $R_x$  and  $T_x$  pins of RFID peruser joined with  $T_x$  and  $R_x$  pins of 8051 Microcontroller individually. At that point the peruser faculties the information from the Tag and transmits the sensed information to microcontroller through serial port.



An inductive vicinity sensor comprises of a loop and ferrite center plan, an oscillator and locator circuit, and a strong state yield. The oscillator makes a high recurrence field transmitting from the loop before the sensor revolved around the pivot of the curl. The ferrite center packages and coordinates the electro-attractive field to the front. At the point when a metal item enters the high-recurrence field, swirl flows are incited on the surface of the target. These outcomes in a loss of vitality in the oscillator circuit and, subsequently, littler abundance of swaying. The locator circuit perceives a particular change in abundance and


produces a sign which will turn the strong state yield "ON" or "OFF". At the point when the metal article leaves the sensing zone, the oscillator recovers, permitting the sensor to come back to its ordinary state.

The IEEE 802.15.4 physical radio determination and works in unlicensed groups worldwide at the accompanying frequencies: 2.400–2.484 GHz, 902-928 MHz and 868.0–868.6 MHz's. The force levels (down from 5 V to 3.3 V) to power the zigbee module.




The correspondence lines (TX, RX, DIN and DOUT) to the proper voltages. The Zigbee module goes about as both transmitter and beneficiary. The Rx and Tx pins of ZIGBEE are joined with Tx and Rx of 8051 microcontroller separately. The information's from microcontroller is serially transmitted to Zigbee module by means of UART port. At that point Zigbee transmits the information to another Zigbee. The information's from Zigbee transmitted from Dout pin. The Zigbee from other side gets the information through Din pin

The LCD standard obliges 3 control lines and 8 I/O lines for the information transport. The 8 information pins are D7:D0. There are two vital registers in the LCD. The RS pin is utilized for their determination. At the point when RS= 0 the Instruction charge code register, permits the client to send summon, for example, clear show, cursor at home, and so on when RS=1 the information register, permit client to send information to be shown at LCD. At the point when RW= 0, the data is being composed on LCD. At the point when RW=1, for perusing from LCD. (Stand out summon that is "Get LCD status" is perused charges all others are compose command)It is a control line. At the point when RW is low (0), the data on the information transport is being composed to the LCD. At the point when RW is high (1), the system is viably questioning (or perusing from) the LCD. One and only guideline ("Get LCD status") is a perused summon. All others are compose orders -so RW will be low for larger part of the time. Empower (En) pin is utilized to tell the LCD that we are sending it information. A high to low heartbeat (of least length 450 ns) preceding sending any charge/ information to LCD. The 8 information lines are joined with PORT 1 of 8051 microcontroller. The three control lines (RS, RW and EN) are joined with PORT 3.5, 3.6 and 3.7 individually



The main pin is ground, second stick is VCC (+5V), third stick is Contrast change, fourth stick is Register Select (R/S), fifth pin is Read/Write (R/W), sixth pin is Clock (Enable), and from seven to fourteen is information pin.


The ARM is a 32-bit diminished direction set PC (RISC) guideline set structural engineering (ISA) grew by ARM Limited. It was known as the Advanced RISC Machine, and before that as the Acorn RISC Machine. The ARM structural engineering is the most broadly utilized 32-bit ISA regarding numbers created. They were initially imagined as a processor for desktop PCs by Acorn Computers, a business now overwhelmed by the x86 family utilized by IBM PC perfect PCs. In any case the relative effortlessness of ARM processors made them suitable for low control applications. This has made them prevailing in the portable and installed hardware advertise as generally ease and little microchips and microcontrollers. This area portrays how to create +5 V DC power supply. The force supply segment is the critical one. It ought to convey steady yield controlled power supply for fruitful working of the undertaking. A 0-12V/1 mA transformer is utilized for this reason. The essential of this transformer is joined into primary supply through on/off switch and wire for shielding from over-burden and short out security. The optional is associated with the diodes to change over 12 V AC to 12 V DC voltage. What's more,



sifted by the capacitors, which is further directed to +5 V, by utilizing IC 7805.

**Remote Section**

From remote segment we can watch the robot exercises through our pc. From CCTV the information is given to the tanker robot in serial configuration. The information is given to PC through remote correspondence zigbee and the information is changed over into feature. The zigbee is in TTL (Transistor Transistor rationale) and our PC is in CMOS (reciprocal metal oxide semiconductor). Since these are two diverse rationales to change over them MAX 232 is utilized.



**MODULES**

Number of Units (Modules) utilized as a part of this segments are power supply unit, microcontroller unit, sensor unit, programming unit.

In Power Supply Unit the air conditioner voltage, commonly 220 V rms is joined with a transformer, which steps that air conditioner voltage down to the level of the converted dc yield. A diode rectifier then gives a full-wave amended voltage that is at first separated by a basic capacitor channel to deliver a dc voltage. This subsequent dc voltage typically has some swell or air conditioning voltage variety. A controller circuit uproots the swells furthermore continues as before dc esteem regardless of the fact that the data dc voltage changes, or the heap associated with the yield

dc voltage changes. This voltage regulation is normally gotten utilizing one of the prevalent voltage controller IC units. The given info is 230 V force supply is given to transformer. From the transformer the yield voltage is produced and expected yield is from the rectifier circuit the 5 V yield will be delivered.

In microcontroller unit the ARM LPC2129 Microcontroller is utilized for getting the information from outer gadgets and 5 V yield is given to the wheel seat robot. In ARM microcontroller the given data is 5 V info is given to the microcontroller from outside gadgets and the normal yield is 5 V yield is delivered by microcontroller and which is given to the outer gadgets.

Here the Sensor unit utilized is metal sensor. The given info is recognized metal protest and send to information microcontroller and the normal yield is based on the distinguished the yield will be delivered.

## RESULTS AND DISCUSSION

We propose another tanker robot to recognize and assault the interloper in the fight zone. We can control the tanker from remote territory utilizing Zigbee remote innovation. Remote CCTV cam is set on the tanker. The CCTV cam collector is joined in remote segment. We viewing the interloper through the CCTV it is consistently checked in remote area. RFID labels are given to our own particular warriors to distinguish inverse officer. RFID peruser is utilized to identify our own particular trooper. Area mine sensor is utilized to distinguish the area mine. The shooting orders given by control area. According to the Corresponding summons got from control area, the robot will shoot the person. So as to control the robot we utilize transfers to run the engine.

## CONCLUSION

Hence, we are going to propose a advanced wireless controlled military tanker robot with gun mechanism to avoid the human losses in battle field. The system can be expanded in future by implementing the latest controller. So, the information will send to the user sections very fast. A distributed version will be designed and implemented. The position of the reference node will be saved and sent to the mobile node in the localization phase. Location-aware computation can be performed on the Zigbee module. Furthermore, the proposed method estimates the location from only a set of RSSI values without using previous RSSI values. Thus, it is also interesting to examine the performance of the target tracking with the proposed method.

## REFERENCES

1. Don Murray and Anup Basu (1994), "Motion Tracking with an Active Camera", *IEEE Transactions on Pattern Analysis and Machine Intelligence*, Vol. 16, No. 5.
2. Fonseca A, Mayron L, Socek D and Marques O (2008), "Design and Implementation of an Optical Flow-Based Autonomous Video Surveillance System", Florida Atlantic University, 777 Glades Rd., Boca Raton, FL 33428 USA (2008).
3. Ismail Oner Sebe (2002), "Object-Tracking Using Multiple Constrains", EE392J, Digital Video Processing, Stanford University, EE Department, Winter.
4. Paul L Rosin (1998), "Thresholding for Change Detection", Department of Information Systems and Computing, Brunel University, Uxbridge, Middlesex UB8 3PH, UK.

5. Prithviraj Banerjee and Somnath Sengupta, "Human Motion Detection and Tracking for Video Surveillance", Department of Electronics and Electrical Communication Engineering, Indian Institute of Technology, Kharagpur, Kharagpur 721302, India.
6. *Robotics and Autonomous Systems - Journal* - Elsevier.



**International Journal of Engineering Research and Science & Technology**

**Hyderabad, INDIA. Ph: +91-09441351700, 09059645577**

**E-mail: editorijerst@gmail.com or editor@ijerst.com**

**Website: www.ijerst.com**

